



## Ducted Quick Connection Guide 2015

Indoor Model Number	Outdoor Model Number	Indoor Static Pressure Modes	Recommended Indoor Static Pressure Range (Pascals)	Supply Air Connection Optional Part	Supply Air Connection Size (mm)	Return Air Connection Size (mm)
<b>ARTG Reverse Cycle Slim Duct &amp; Slimline - Single Phase</b>						
ARTG09LLLB	AOTG09LBCA	10	0 to 90	-	650 x 151	Bulkhead
ARTG12LLLB	AOTG12LBCA	10	0 to 90	-	650 x 151	Bulkhead
ARTG18LLTA	AOTG18LACC	10	0 to 90	-	850 x 151	Bulkhead
ARTG24LMLC	AOTG24LATC	4	30 to 150	UTD-RF204	205 (4)	1015 x 240
				UTD-SF045T	1065 x 204	
<b>ARTG Reverse Cycle High Static Ducted - Single Phase (NEW)</b>						
ARTG45LDTA	AOTG45LBTA	20	60 - 250	-	1162 x 277	1295 x 316
ARTG54LDTA	AOTG54LBTA	20	60 - 250	-	1162 x 277	1295 x 316
ARTG60LDTA	AOTG60LBTA	20	60 - 250	-	1162 x 277	1295 x 316
<b>ARTA Reverse Cycle Slimline Ducted Inverter - Single Phase</b>						
ARTA30LBTU	AOTA30LBTL	4	30 to 150	UTD-RF204	205 (4)	1015 x 240
				UTD-SF045T	1065 x 204	
ARTA36LATU	AOTA36LBTL	4	30 to 150	UTD-RF204	205 (4)	1015 x 240
				UTD-SF045T	1065 x 204	
ARTA45LATU	AOTA45LBTL	4	30 to 150	UTD-RF204	205 (4)	1015 x 240
				UTD-SF045T	1065 x 204	
<b>ARTG Reverse Cycle High Static Ducted Inverter - Single Phase</b>						
ARTG30LHTA	AOTG30LATL	4	60 to 210	-	850 x 295	865 x 325
ARTG36LHTA	AOTG36LATL	4	60 to 210	-	850 x 295	865 x 325
ARTG45LHTA	AOTG45LATL	4	60 to 260	-	921 x 304	1062 x 351
ARTG54LHTC	AOTG54LATL	4	60 to 260	-	921 x 304	1062 x 351
ARTG60LHTB	AOTG60LATA	4	50 to 260	-	1200 x 350	1250 x 370
<b>ARTG / ARTC Reverse Cycle High Static Ducted Inverter - Three Phase</b>						
ARTG36LHTB	AOTG36LATT	4	60 to 210	-	851 x 295	862 x 324
ARTG45LHTB	AOTG54LATT	4	60 to 260	-	921 x 304	1062 x 351
ARTG60LHTA	AOTG60LATT	4	60 to 260	-	921 x 304	1062 x 351
ARTC72LATU	AOTA72LALT	5	50 to 250	-	1200 x 350	1251 x 370
ARTC90LATU	AOTA90LALT	5	50 to 250	-	1200 x 350	1251 x 470
<b>Inverter Multi - ARTG Bulkhead Ducted Indoor Units</b>						
ARTG09LLLB	AOTG24LAT3 AOTG30LBTA4	10	0 to 40	-	650 x 151	Bulkhead
ARTG12LLLB		10	0 to 90	-	650 x 151	Bulkhead
ARTG18LLTA		10	0 to 90	-	850 x 151	Bulkhead

Indoor Model Number	Outdoor Model Number	Indoor Static Pressure Modes	Recommended Indoor Static Pressure Range (Pascals)	Supply Air Connection Optional Part	Supply Air Connection Size (mm)	Return Air Connection Size (mm)
<b>VRF Bulkhead Ducted</b>						
ARXB07GALH	-	2	0 to 50	-	400 x 150	Bulkhead
ARXB09GALH	-	2	0 to 50	-	400 x 150	Bulkhead
ARXB12GALH	-	2	0 to 50	-	600 x 150	Bulkhead
ARXB14GALH	-	2	0 to 50	-	600 x 150	Bulkhead
ARXB18GALH	-	2	0 to 50	-	600 x 150	Bulkhead
<b>VRF Slimline Ducted</b>						
ARXA24GALH	-	1	30 to 150	UTD-RF204	205 (4)	1015 x 240
				UTD-SF045T	1065 x 204	
ARXA30GALH	-	1	30 to 150	UTD-RF204	205 (4)	1015 x 240
				UTD-SF045T	1065 x 204	
ARXA36GALH	-	1	30 to 150	UTD-RF204	205 (4)	1015 x 240
				UTD-SF045T	1065 x 204	
ARXA45GALH	-	1	30 to 150	UTD-RF204	205 (4)	1015 x 240
				UTD-SF045T	1065 x 204	
<b>VRF Slimline Ducted - Low Static Model</b>						
ARXB36GALH	-	2	0 to 80	UTD-RF204	205 (4)	1015 x 240
				UTD-SF045T	1065 x 204	
ARXB45GALH	-	2	0 to 80	UTD-RF204	205 (4)	1015 x 240
				UTD-SF045T	1065 x 204	
<b>VRF High Static Model</b>						
ARXC36GATH	-	1	100 to 200	-	851 x 295	862 x 324
ARXC45GATH	-	1	100 to 250	-	851 x 295	862 x 324
ARXC60GATH	-	1	100 to 250	-	851 x 295	862 x 324
ARXC72GATH	-	2	50 to 300	-	1199 x 350	1251 x 370
ARXC90GATH	-	2	100 to 300	-	1199 x 350	1251 x 370
<b>VRF Low Static Pressures</b>						
ARXD07GALH	-	9	0 to 90	-	650 x 151	Bulkhead
ARXD09GALH	-	9	0 to 90	-	650 x 151	Bulkhead
ARXD12GALH	-	9	0 to 90	-	650 x 151	Bulkhead
ARXD14GALH	-	9	0 to 90	-	650 x 151	Bulkhead
ARXD18GALH	-	9	0 to 90	-	850 x 151	Bulkhead
ARXD24GALH	-	9	0 to 50	-	1050 x 151	Bulkhead